

MONO MULTY CRYSTALLINE SOLAR PHOTOVOLTAIC MODULE - 12Wp, 12V



MODEL NAME- AE112

Photovoltaic Modules- Salient Features

Solar cells are encapsulated between tempered glass and EVA pottant with PVF back sheet to provide maximum protection from the severest environmental conditions.

The laminate framed using anodized aluminum frame to provide structural strength and ease of installation.

Specifications#

ELECTRICAL SPECIFICATIONS :

Model - AE112	Power	
Power (Max)	Pp (watts)	12Wp
Voltage at rated power	Vld (Volts)	16.4 V
Voltage at maximum power	Vmp (volts)	> 15.0 V
Current at maximum power	Imp (amps)	0.73 A
Open circuit voltage	Voc (volts)	20.0 V
Short circuit current	Isc (amps)	0.85 A
Solar Cells per Module	Units	36
Type of Solar Cell : Mono / Multi Crystalline		

DIMENSIONS AND WEIGHT :

Length	mm (Inches)	415 (16.20) ±1
Width	mm (Inches)	335 (13.18) ±0.5
Thickness	mm (Inches)	22 (0.86) ±0.5
Weight	kg (lbs)	1.40 (3.02) ±5%
Area	Sq.meters (Sq.Ft)	0.14(1.49)

Note:

Our standard range of modules are supplied without blocking diodes. However, we will supply with blocking diodes on specific customer request.

Quality Assurance

Andromeda monocrystalline photovoltaic modules meet and exceed specifications for the following tests.

- Thermal cycling test
- Thermal shock test
- Thermal / Freezing and high humidity cycling test
- Electrical isolation test
- Hail impact test
- Mechanical, wind and twist loading test
- Salt spray test
- Light and water-exposure test
- Field exposure test
- Specifications subject to without notice during product upgradations

Please Click Here For [Module Mounting Details](#)



Andromeda Energy Technologies (P) Ltd

No - 4, First Floor, SP Road, Opp. Civil Court
Secunderabad - 500003.Andhra Pradesh
INDIA .

Phone :+91 40 - 27803147

Fax : +91 40 - 66260277

Cell:+91 9849490289

e-mail : info@andromedasolar.com

www.andromedasolar.com