

MONO MULTY CRYSTALLINE SOLAR PHOTOVOLTAIC MODULE - 14Wp&15WP, 12V



MODEL NAME - AF112, AG112

Photovoltaic Modules- Salient Features

Solar cells are encapsulated between tempered glass and EVA pottant with PVF back sheet to provide maximum protection from the severest environmental conditions.

The laminate framed using anodized aluminum frame to provide structural strength and ease of installation.

Specifications#

ELECTRICAL SPECIFICATIONS :			DIMENSIONS AND WEIGHT :		
Model - AF112	Power		Length	mm (Inches)	635 (25.03)±1
Power (Max)	Pp (watts)	14Wp	Width	mm (Inches)	275(10.82) ±0.5
Voltage at rated power	Vld (Volts)	16.4 V	Thickness	mm (Inches)	22(0.866) ±0.5
Voltage at maximum power	Vmp (volts)	> 15.0 V	Weight	kg (lbs)	2.10(4.53) ±5%
Current at maximum power	Imp (amps)	0.81A	Area	Sq.meters (Sq.Ft)	0.21(2.26)
Open circuit voltage	Voc (volts)	20.0V			
Short circuit current	Isc (amps)	1.00A			
Solar Cells per Module	Units	36			
Type of Solar Cell : Mono / Multi Crystalline					
Model - AG112			Length	mm (Inches)	635 (25.03)±1
Power (Max)	Pp (watts)	14Wp	Width	mm (Inches)	275(10.82) ±0.5
Voltage at rated power	Vld (Volts)	16.4 V	Thickness	mm (Inches)	22(0.866) ±0.5
Voltage at maximum power	Vmp (volts)	> 15.0 V	Weight	kg (lbs)	2.10(4.53) ±5%
Current at maximum power	Imp (amps)	0.90A	Area	Sq.meters (Sq.Ft)	0.21(2.26)
Open circuit voltage	Voc (volts)	20.0V			
Short circuit current	Isc (amps)	1.00A			
Solar Cells per Module	Units	36			

Note:

Our standard range of modules are supplied without blocking diodes. However, we will supply with blocking diodes on specific customer request.

Quality Assurance

Andromeda monocrystalline photovoltaic modules meet and exceed specifications for the following tests.

- Thermal cycling test
- Thermal shock test
- Thermal / Freezing and high humidity cycling test
- Electrical isolation test
- Hail impact test
- Mechanical, wind and twist loading test
- Salt spray test
- Light and water-exposure test
- Field exposure test
- Specifications subject to without notice during product upgradations

Module Mounting Details



Andromeda Energy Technologies (P) Ltd

No - 4, First Floor, SP Road, Opp. Civil Court
Secunderabad - 500003, Andhra Pradesh
INDIA .

Phone : +91 40 - 27803147

Fax : +91 40 - 66260277

Cel l: +91 9948333284

e-mail : info@andromedasolar.com

www.andromedasolar.com