

MONO/ MULTY CRYSTALLINE SOLAR PHOTOVOLTAIC MODULE - 80WP&100WP&110WP



MODEL NO - AQ112, AR112, AS112

Photovoltaic Modules- Salient Features

Solar cells are encapsulated between tempered glass and EVA pottant with PVF back sheet to provide maximum protection from the severest environmental conditions.

The laminate framed using anodized aluminum frame to provide structural strength and ease of installation.

Specifications#

ELECTRICAL SPECIFICATIONS :			DIMENSIONS AND WEIGHT :		
Model - AQ112	Power				
Power (Max)	Pp (watts)	80Wp	Length	mm (Inches)	1486(58.50) ±1
Voltage at rated power	Vld (Volts)	16.4 V	Width	mm (Inches)	655(25.78) ±0.5
Voltage at maximum power	Vmp (volts)	> 15.0 V	Thickness	mm (Inches)	34 (1.33) ±0.5)
Current at maximum power	Imp (amps)	4.70 A	Weight	kg (lbs)	12.50(27.05)±5%
Open circuit voltage	Voc (volts)	20 V	Area	Sq.meters (Sq.Ft)	0.97 (10.47)
Short circuit current	Isc (amps)	5.10 A			
Solar Cells per Module	Units	36			
Type of Solar Cell : Mono / Multi Crystalline					
Model - AR112					
Power (Max)	Pp (watts)	100Wp	Length	mm (Inches)	1486(58.50) ±1
Voltage at rated power	Vld (Volts)	16.4 V	Width	mm (Inches)	655(25.78) ±0.5
Voltage at maximum power	Vmp (volts)	> 15.0 V	Thickness	mm (Inches)	34 (1.33) ±0.5)
Current at maximum power	Imp (amps)	6.10 A	Weight	kg (lbs)	12.50(27.05)±5%
Open circuit voltage	Voc (volts)	20 V	Area	Sq.meters (Sq.Ft)	0.97 (10.47)
Short circuit current	Isc (amps)	6.50 A			
Solar Cells per Module	Units	36			
Type of Solar Cell : Mono / Multi Crystalline					
Model - AS112					
Power (Max)	Pp (watts)	110Wp	Length	mm (Inches)	1486(58.50) ±1
Voltage at rated power	Vld (Volts)	16.4 V	Width	mm (Inches)	655(25.78) ±0.5
Voltage at maximum power	Vmp (volts)	> 15.0 V	Thickness	mm (Inches)	34 (1.33) ±0.5)
Current at maximum power	Imp (amps)	6.70 A	Weight	kg (lbs)	12.50(27.05)±5%
Open circuit voltage	Voc (volts)	20 V	Area	Sq.meters (Sq.Ft)	0.97 (10.47)
Short circuit current	Isc (amps)	7.20 A			
Solar Cells per Module	Units	36			

Note:

Our standard range of modules are supplied without blocking diodes. However, we will supply with blocking diodes on specific customer request.

Quality Assurance

Andromeda monocrystalline photovoltaic modules meet and exceed specifications for the following tests

- Thermal cycling test
- Thermal shock test
- Thermal / Freezing and high humidity cycling test
- Electrical isolation test
- Hail impact test
- Mechanical, wind and twist loading test
- Salt spray test
- Light and water-exposure test
- Field exposure test
- Specifications subject to without notice during product upgradations

Please Click Here For [Module Mounting Details](#)



Andromeda Energy Technologies (P) Ltd

No - 4, First Floor, SP Road, Opp. Civil Court
Secunderabad - 500003.Andhra Pradesh
INDIA .
Phone :+91 40 - 27803147
Fax : +91 40 - 66260277
Cell:+91 9948333284
e-mail : info@andromedasolar.com
www.andromedasolar.com